


Material Safety Data Sheet

Used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200



SECTION I - NAME AND PRODUCT
<p>Company Name: Flexovit Abrasives</p> <p>Address: 1305 Eden-Evans Road Angola, NY 14006</p> <p>Phone: 800-689-3539</p> <p>Date Updated: 4/1/06</p> <p>Product: Ceramic Resin Fiber Discs</p>

SECTION II - COMPOSITION							
--------------------------	--	--	--	--	--	--	--

Ingredient	% By Weight	OSHA Regulate	Cas #	OSHA PEL	ACGIH TLV	Other Limits	Carcinogen
Paper (Cloth cotton, polyester) -Vulcanized Fiber	10-35	N/A	N/A	N/A	N/A	N/A	No
Animal Hide Glues	N/A	N/A	N/A	N/A	N/A	N/A	No
Cured Phenoloic Resins	20-30	N/A	N/A	N/A	N/A	N/A	No
Aluminium Oxide	90	N/A	1344-28-1	N/A	N/A	N/A	No
Magnesium Oxide	0.5	N/A	1309-48-4	N/A	N/A	N/A	No
Iron Oxide (Fe ₂ O ₃)	0.5	N/A	1309-37-1	N/A	N/A	N/A	No

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS			
---	--	--	--

Physical State	N/A	Boiling Point	N/A	Specific Gravity (H ₂ O=1)	N/A
Vapor Pressure (mm HG)	N/A	Freezing Point	N/A	Odor Threshold	N/A
Vapor Density (Air=1)	N/A	Melting Point	N/A	pH	N/A
Solubility in Water	N/A	% Volatile	N/A	Evaporation Rate	N/A
Odor/Appearance	N/A	Coefficient of Water/Oil Distribution			N/A

SECTION IV - FIRE AND EXPLOSION DATA			
--------------------------------------	--	--	--

Means Of Extinction: Non-combustable. Choose material suitable for surrounding fire	Lower And Upper Explosion Limits	N/A
Flammable Limits	N/A	Special Fire Fighting Procedures
Flash Point	N/A	Unusual Fire or Explosion Hazards

SECTION V - REACTIVITY DATA

Stability: Stable

Incompatibility (Materials to Avoid): N/A

Hazardous Decomposition or Byproducts: N/A

Hazardous Polymerization: Will not occur

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry	Signs and Symptoms of Exposure	Emergency & First-Aid Procedures
Eye & Skin Contact	Eye-Redness, swelling, pain, & tearing Skin-Itching	Immediately flush with large amounts of water. Get immediate medical attention.
Inhalation	Fibrosis (General): shortness of breath & persistent coughing. Irritation (Upper respiratory): soreness of nose & throat, coughing & sneezing	Remove to fresh air. If symptoms continue, get medical attention.
Ingestion	Irritation of gastrointestinal tissues: pain, vomiting, abdominal tenderness, nausea, blood in vomitus & blood in feces	Do not induce vomiting. Drink two glasses of water & call a physician.

SECTION VII- STORAGE HANDLING AND USE PROCEDURES

Steps to be taken in case material is released or spilled: Observe precautions from other sections. Collect spilled material.
Place in a closed container.

Waste Disposal Method: Consult applicable regulations or authorities before disposal.

Precautions to be taken in handling and storing: Store at 35% to 50% relative humidity and 60⁰ to 80⁰ F with adequate
ventilation.

Other precautions: Use CAMI (Coated Abrasive Mfg. Institute) Guidelines

SECTION VIII- CONTROL MEASURES

Protection	Requirements and Referrals
Respiratory	Avoid breathing dust
Ventilation	Local Exhaust: Normal Duct Procedure
Protective Gloves	Recommended
Eye Protection	ANSI Standard 287.1 impact resistant protective lenses
Hearing Protection	As deemed necessary
Hygienic Practices	N/A
Other	N/A

COMPANY USE

The information and recommendations set forth herein are taken from sources and references believed to be accurate and complete as of the date hereof. However, FlexOvit® U.S.A., Inc. makes no expressed or implied warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.