



**SECTION VI - HEALTH HAZARD DATA**

<b>Route(s) of Entry</b>	<b>Signs and Symptoms of Exposure</b>	<b>Emergency &amp; First-Aid Procedures</b>
Inhalation	Choking sensation if allowed to become very dusty Nuisance dust: respirable-5 mg/m <sup>3</sup> , total-15 mg/m <sup>3</sup>	As deemed necessary
Eyes	May become irritated	As deemed necessary
Skin	May become irritated by abrasion	As deemed necessary

**SECTION VII- STORAGE HANDLING AND USE PROCEDURES**

Steps to be taken in case material is released or spilled: Does not apply

Waste Disposal Method: No special procedure, standard landfill consistent with applicable state and local laws

Precautions to be taken in handling and storing: Store at 35-50% relative humidity and 60 to 80 degrees F with adequate ventilation.

Other Precautions: Use CAMI (Coated Abrasive MFG Institute) guidelines

**SECTION VIII- CONTROL MEASURES**

<b>Protection</b>	<b>Requirements and Referrals</b>
Respiratory	Avoid breathing dust
Ventilation	Normal dust procedure
Protective Gloves	Recommended when grinding
Eye Protection	Impact resistant protective glasses w/side shield (ANSI Z87.1)
Hearing Protection	As deemed necessary
Hygienic Practices	N/A
Other	As deemed necessary

**COMPANY USE**

The information and recommendations set forth herein are taken from sources and references believed to be accurate & complete as of the date hereof. However, Flexovit® U.S.A., Inc. makes no expressed or implied warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.